


Hune *†*	SKU	AT-ACC-CA-363
----------	-----	---------------

Product	Cables Braided Type C - Type C - 1.2m	
Category	Accessories	
Sub category	Type C	

Item	Actual value
Physical characteristics	
<i>Available colors</i>	Black+Green
<i>Weight</i>	26.8gram
<i>Diameter</i>	3.8mm
<i>Nylon thread</i>	YES
Electrical specifications	
<i>Dielectric Strength (V)</i>	500VDC
<i>Insulation Resistance</i>	20M Ohm
<i>Conductor resistance</i>	inside 10Ohm
<i>Attenuation</i>	N/A
<i>Input Current</i>	3A
<i>Operating temperature range</i>	0-45°C
<i>Impedance (Ω ± Ω)</i>	inside 50mOhm

<i>Voltage rating (V):</i>	5V
<i>Drain</i>	0.4V
<i>Time Delay Skew within a pair</i>	100pS
<i>Data transfer support(Mbps)</i>	480Mb/s
Uncategorized	
<i>Certifications</i>	-
Accessories	
<i>Name accesories</i>	charging cable
<i>Cable length</i>	1.2m
<i>Cable type</i>	charging cable
<i>Cable wire gauge</i>	68*0.08mm*2BC+16*0.08mm*3BC+AB32*0.08mm*TC+AI Foil+Nylon Silk250D
<i>Cable shield type</i>	Tinned copper mesh braided shield
Cables	
<i>Cable characteristics</i>	copper wires
<i>Cable connector A (type) / B (type)</i>	USB-C to USB-C
<i>Cable connector plating</i>	Nickel/SUS/Alloy
Jacket: Material	
<i>Jacket: Material</i>	RTPE
Jacket: Thickness	
<i>Jacket: Thickness</i>	Dim.8.5MM
Jacket: Hardness	
<i>Jacket: Hardness</i>	80A
Jacket: Tensile Strength	
<i>Jacket: Tensile Strength</i>	N/A
Jacket: Elongation	
<i>Jacket: Elongation</i>	N/A
Jacket: Flame Test	
<i>Jacket: Flame Test</i>	N/A
Spark test	
<i>Spark test</i>	1500V ok
Ports / Plugs	
<i>Input plug 1 Type</i>	USB-C
<i>Output plug 1 Type</i>	USB-C
<i>Plug type</i>	USB
<i>Plug Material</i>	RTPE+RPET
<i>Plug plating</i>	SUS

