


Hune * *	SKU	AT-ACC-CA-364
----------	-----	---------------

Product	Cables Braided Type C - Lightning - 1.2m	
Category	Accessories	
Sub category	Type C	

Item	Actual value
Physical characteristics	
Available colors	Green
Weight	26.8gram
Diameter	3.8mm
Nylon thread	Yes
Electrical specifications	
Dielectric Strength (V)	500VDC
Insulation Resistance	20M Ohm
Conductor resistance	inside 10hm
Attenuation	N/A
Input Current	3A
Operating temperature range	0-45°C
Plug plating	SUS+Alloy

Impedance ($\Omega \pm \Omega$)	inside 50mOhm
Voltage rating (V):	5V
Drain	0.4V
Time Delay Skew within a pair	100pS
Data transfer support(Mbps)	480Mb/s
Uncategorized	
Certifications	-
Accessories	
Name accessories	charging cable
Cable length	1.2m
Cable type	charging cable
Cable wire gauge	68*0.08mm*2BC+16*0.08mm*3BC+AB32*0.08mm*TC+Al Foil+ Nylon Silk 250D
Cable shield type	Tinned copper mesh braided shield
Cables	
Cable characteristics	copper wires
Cable connector A (type) / B (type)	USB-C to Lightning
Cable connector plating	Nickel/SUS/Alloy
Jacket: Material	RTPE
Jacket: Thickness	Dim.8.5MM
Jacket: Hardness	80A
Jacket: Tensile Strength	N/A
Bending Test	20000
Jacket: Flame Test	N/A
Spark test	1500V ok
Ports / Plugs	
Input plug 1 Type	USB-C
Output plug 1 Type	Lightning
Plug type	USB
Plug Material	RTPE+RPET



