FAB10LBL6

T	
Type	Dofri
Product Family	Refrigerator
Installation	Free Standing
Category	One Door
Reference width	Until 60
Reference height	Until 100
Cooling type	Static
Defrost	Automatic for refrigerator, manual for freezer
Door opening flush with the wall	No
Slot-in	No
Hinge type	Standard
Hinge position	Left
· .	
Reversible door EAN code	No 8017709342357
Aesthetics	FOIo Stulo
Aesthetics	50's Style
Colour	Black
Finishing	Gloss
Design	Rounded
Material	Heat-moulded
Handle kit to be ordered separately	No
Handle	External
Handle type	Fixed
Logo colour	Chrome
Handle colour	
	Chrome
Side material	Steel
Side colour	Black
Logo	Applied
Door shelves profile colour	Silver
Colour of glass shelf profile	Silver
Display	No
Dispenser	No
Water Filter	No
HomeBar	No
5.00	
Refrigerator compartment features	
No. of adjustable shelves	1
Number of fruit and vegetables drawers	1
Type of crisper/vegetable drawers cover	Standard
Type of adjustable shelves	Glass
Crisper Cover	Yes
Bottle shelf	No
Type of crisper/vegetable drawers cover	Glass
No. of lights	1
=	
Convertible temperature drawer	No
Life Plus zone-0°C	No
Low temperature compartment	No
Internal light in fridge	Yes
Type of internal light (fridge)	LED
Refrigerator Inner Door	
No. of door shelves with transparent cover	0
Number of adjustable door shelves	2
No. of bottle shelves	1
Other Petricovetor features	
Other Refrigerator features	No
Natural Plus Blu Light	No
MultiFlow	No
Fan	No
Ionizer	No
Titanium tech	No
Antibacterial odour filter	No
Bio Care Zone	
	No
Erector compartment features	No
Freezer compartment features Internal freezer compartment	
Freezer compartment features Internal freezer compartment Internal light in freezer	No Yes No

Other technical features	
Water network connection	No
Power on lamp	No
Temperature alarm lamp	No
Door open alarm	No
Temperature Alarm	No
Type of temperature control	Electro-mechanical
No. of compressors	1
·	R600a
Refrigerant gas type	
Type of compressor	Standard
Refrigerant Quantity (gr)	25 g
Foam agent	Cyclopentane
Metal backpanel material	Aluminium Foil
Desferons and / Francischel	
Performance / Energy Label	Defei
Category of the household refrigerating appliance model	Refrigerator - freezer
Energy efficiency Index EEI	
Fresh Food compartments (Chiller incl.) - Gross Volume	
Climatic class	N, ST, T
Fresh Food compartment - Storage Volume	104.8
Total gross volume	118
Storage volume frozen food compartment	17 l
4 Star compartment - Star rating	4
Freezing capacity	2.59 Kg/24h
	_
Total storage volume	121.8
Thaw time	6 h
Performance / Energy Label NEW	
Annual energy consumption	115 kWh/Jahr
Energy efficiency class	D
Airborne acoustical noise emission class	В
Total volume	122
Sum of the volumes of the frozen compartment(s)	17
Sum of the volumes of the chill compartment(s) and the unfrozen compartment(s)	105
Total volume	01
Noise level	35 dB(A) re 1pW
Thaw time	6 h
4 star - Freezing capacity	2.6 Kg/24h
	- 0/
	N ST T
Climatic class	N, ST, T 79 %
Climatic class	
Climatic class EEI Electrical Connection	79 %
Climatic class EEI Electrical Connection Nominal power	79 % 50 W
Climatic class EEI Electrical Connection Nominal power	79 %
Climatic class EEI Electrical Connection Nominal power Current	79 % 50 W
Climatic class EEI Electrical Connection Nominal power Current Voltage (V)	79 % 50 W 0.42 A
Climatic class EEI Electrical Connection Nominal power Current Voltage (V) Frequency (Hz)	79 % 50 W 0.42 A 220-240 V
Climatic class EEI Electrical Connection Nominal power Current Voltage (V) Frequency (Hz) Power supply cable length	79 % 50 W 0.42 A 220-240 V 50 Hz
Climatic class EEI Electrical Connection Nominal power Current Voltage (V) Frequency (Hz) Power supply cable length Printed Documents	79 % 50 W 0.42 A 220-240 V 50 Hz 180 cm
Climatic class EEI Electrical Connection Nominal power Current Voltage (V) Frequency (Hz) Power supply cable length Printed Documents	79 % 50 W 0.42 A 220-240 V 50 Hz
Climatic class EEI Electrical Connection Nominal power Current Voltage (V) Frequency (Hz) Power supply cable length Printed Documents Sticker	79 % 50 W 0.42 A 220-240 V 50 Hz 180 cm
Climatic class EEI Electrical Connection Nominal power Current Voltage (V) Frequency (Hz) Power supply cable length Printed Documents Sticker Optional accessories	79 % 50 W 0.42 A 220-240 V 50 Hz 180 cm
Climatic class EEI Electrical Connection Nominal power Current Voltage (V) Frequency (Hz) Power supply cable length Printed Documents Sticker Optional accessories	79 % 50 W 0.42 A 220-240 V 50 Hz 180 cm
Climatic class EEI Electrical Connection Nominal power Current Voltage (V) Frequency (Hz) Power supply cable length Printed Documents Sticker Optional accessories Accessories not included	79 % 50 W 0.42 A 220-240 V 50 Hz 180 cm
Climatic class EEI Electrical Connection Nominal power Current Voltage (V) Frequency (Hz) Power supply cable length Printed Documents Sticker Optional accessories Accessories not included Logistic Information	79 % 50 W 0.42 A 220-240 V 50 Hz 180 cm
Climatic class EEI Electrical Connection Nominal power Current Voltage (V) Frequency (Hz) Power supply cable length Printed Documents Sticker Optional accessories Accessories not included Logistic Information Width (mm)	79 % 50 W 0.42 A 220-240 V 50 Hz 180 cm No
Climatic class EEI Electrical Connection Nominal power Current Voltage (V) Frequency (Hz) Power supply cable length Printed Documents Sticker Optional accessories Accessories not included Logistic Information Width (mm) Depth without handle	79 % 50 W 0.42 A 220-240 V 50 Hz 180 cm No
Climatic class EEI Electrical Connection Nominal power Current Voltage (V) Frequency (Hz) Power supply cable length Printed Documents Sticker Optional accessories Accessories not included Logistic Information Width (mm) Depth without handle Product Height with feet	79 % 50 W 0.42 A 220-240 V 50 Hz 180 cm No no
Climatic class EEI Electrical Connection Nominal power Current Voltage (V) Frequency (Hz) Power supply cable length Printed Documents Sticker Optional accessories Accessories not included Logistic Information Width (mm) Depth without handle Product Height with feet Product width with maximum doors opening	79 % 50 W 0.42 A 220-240 V 50 Hz 180 cm No No 970 mm 842 mm
Climatic class EEI Electrical Connection Nominal power Current Voltage (V) Frequency (Hz) Power supply cable length Printed Documents Sticker Optional accessories Accessories not included Logistic Information Width (mm) Depth without handle Product Height with feet Product width with maximum doors opening Product depth with handle	79 % 50 W 0.42 A 220-240 V 50 Hz 180 cm No No 970 mm 842 mm 701 mm
Climatic class EEI Electrical Connection Nominal power Current Voltage (V) Frequency (Hz) Power supply cable length Printed Documents Sticker Optional accessories Accessories not included Logistic Information Width (mm) Depth without handle Product Height with feet Product width with maximum doors opening Product depth with handle	79 % 50 W 0.42 A 220-240 V 50 Hz 180 cm No No 970 mm 842 mm
Climatic class EEI Electrical Connection Nominal power Current Voltage (V) Frequency (Hz) Power supply cable length Printed Documents Sticker Optional accessories Accessories not included Logistic Information Width (mm) Depth without handle Product Height with feet Product width with maximum doors opening Product depth with doors open at 90°	79 % 50 W 0.42 A 220-240 V 50 Hz 180 cm No No 970 mm 842 mm 701 mm
Climatic class EEI Electrical Connection Nominal power Current Voltage (V) Frequency (Hz) Power supply cable length Printed Documents Sticker Optional accessories Accessories not included Logistic Information Width (mm) Depth without handle Product Height with feet Product width with maximum doors opening Product depth with doors open at 90° No longer in use	79 % 50 W 0.42 A 220-240 V 50 Hz 180 cm No no 545 mm 659 mm 970 mm 842 mm 701 mm 1085 mm
Climatic class EEI Electrical Connection Nominal power Current Voltage (V) Frequency (Hz) Power supply cable length Printed Documents Sticker Optional accessories Accessories not included Logistic Information Width (mm) Depth without handle Product Height with feet Product width with maximum doors opening Product depth with doors open at 90°	79 % 50 W 0.42 A 220-240 V 50 Hz 180 cm No No 100 100 100 100 100 100

Logistic Information	
EAN code	8017709342357
Width (mm)	545 mm
Depth without handle	659 mm
Product Height with feet	970 mm
Product width with maximum doors opening	842 mm
Product depth with handle	701 mm
Product depth with doors open at 90°	1085 mm
Dimensions	970x545x659 mm
Packed width	630 mm
Packaged depth	760 mm
Height (mm) packed	1105 mm
Dimensions of the packed product (mm)	1105X630X760 mm
Quantity per container (20 cf)	
Quantity per container (40 cf)	
Quantity per container (40 HC)	
Net weight (kg)	43.000 kg
Gross weight (kg)	52.000 kg
Maximum stackability	4

Maximum stackability4Type of packagingCardboardPackaging composition - paper & cardboard2.686 kgPackaging composition - polystyrene (kg)0.547 kgPackaging composition - wood (kg)7.184 kgPackaging composition - plastic (kg)0.237 kgPackaging with fumigated woodYRaee CodeF2